










Tensors: A Better Way to Pull it All Together

Model Number	Safe Working Load (lbs)	Chain Size (in.)	Standard Adjustment (in.)	Chain Length (in.)	Approximate Weight with 8" Adjustment (lbs.)
T-2 	5,400	3/8	6 thru 14	N/A	14
	9,000	1/2	6 thru 14	N/A	16
	15,000	5/8	6 thru 14	N/A	22
	20,000	3/4	6 thru 14	N/A	40
T-3 	5,400	3/8	6 thru 14	N/A	16
	9,000	1/2	6 thru 14	N/A	20
	15,000	5/8	6 thru 14	N/A	27
	20,000	3/4	6 thru 14	N/A	45
T-5 	5,400	3/8	6 thru 14	N/A	19
	9,000	1/2	6 thru 14	N/A	21
	15,000	5/8	6 thru 14	N/A	25
	20,000	3/4	6 thru 14	N/A	43
T-7 	5,400	3/8	6 thru 14	N/A	19
	9,000	1/2	6 thru 14	N/A	21
	15,000	5/8	6 thru 14	N/A	25
	20,000	3/4	6 thru 14	N/A	43
T-8 	5,400	3/8	6 thru 14	N/A	18
	9,000	1/2	6 thru 14	N/A	20
	15,000	5/8	6 thru 14	N/A	25
	20,000	3/4	6 thru 14	N/A	43
T-10 	5,400	3/8	6 thru 14	N/A	34
	9,000	1/2	6 thru 14	N/A	44
	15,000	5/8	6 thru 14	N/A	58
	20,000	3/4	6 thru 14	N/A	70
T-33 T-200 T-33 T-200 	9,000	1/2	13	84 and 24	44
	9,000	1/2	13	12 and 12	30
	15,000	5/8	13	84 and 24	70
	15,000	5/8	13	12 and 12	41

9.1.2011 Revision 1

